# 4-Channel Stereo Headphone Amplifier

-10 20

### **IMPORTANT SAFETY INSTRUCTIONS**

- 1. Read Instructions All the safety and operating instructions should be ead before the appliance is operated.
- 2. Retain Instructions The safety and operating instructions should be retained for future reference.
- **3. Heed Warnings** All warnings on the appliance and in the operating instructions should be adhered to.
- 4. Follow Instructions All operating and use instructions should be followed.
- Water and Moisture 
  — The appliance should not be used near water -for example, near a bathtub, washbowl, kitchen sink, laundry tub, swimming pool, or a wet basement.
- 6. Ventilation The appliance should be situated so that its location or position does not interfere with its proper ventilation. For example, the appliance should not be situated on a bed, sofa, rug, or similar surface that may block the ventilation openings: or placed in a built-in installation, such as a bookcase or cabinet that may impede the flow of air through the ventilation openings.
- Heat The appliance should be situated away from heat sources such as radiators, heat registers, stoves, or other appliances (including amplifiers) that produce heat.
- Grounding or Polarization Precaution should be taken to insure that the grounding or polarization means of an appliance is not defeated.
- 10. Power-Cord Protection Power supply cords should be routed so that they are not likely to be walked on or pinched by items placed upon or against them, paying particular attention to cords at plugs, convenience receptacles, and the point at which they exit from the appliance.
- 11. Cleaning The appliance should be cleaned only as recommended by the manufacturer.
- 12. Power Lines An outside antenna system should not be located in the vicinity of overhead power lines or other electric light or power circuits, or where it can fall into such power lines or circuits. When installing an outside antenna system, extreme care should be taken to keep from touching such power lines or circuits as contact with them might be fatal.
- 13. Nonuse Periods The power cord of the appliance should be unplugged from the outlet when the appliance is to be left unused for a long period of time.
- **14. Object and Liquid Entry** Care should be taken so that objects do not fall and liquids are not spilled into the enclosure through openings.
- 15. Carts and Stands If the appliance is used with a cart or stand, the cart or stand should be a type recommended by the manufacturer. An appliance and cart combination should be moved with care. Quick stops, excessive force, and uneven surfaces



- cause the appliance and cart combination to overturn.
- **16. Mounting** The appliance should be mounted only as recommended by the manufacturer.
- 17. Damage Requiring Service The appliance should be serviced by qualified service personnel when:
  - A. The power-supply cord or plug has been damaged.
  - B. Objects have fallen into, or liquid has been spilled into the appliance enclosure.
  - C. The appliance has been exposed to rain.
  - D. The appliance has been dropped, or the enclosure damaged.
  - E. The appliance does not appear to operate normally or exhibits a marked change in performance.

- Servicing The user should not attempt to service the appliance beyond that described in the user's operating instructions. All other servicing should be referred to qualified personnel.
- Overloading Do not overload wall outlets and extension cords as this can result in a risk of fire or electric shock.
- 20. Replacement Parts When replacement parts are required, be sure the service technician has used replacement parts specified by the manufacturer or have the same characteristics as the original part. Unauthorized substitutions may result in fire, electric shock or other hazards.
- 21. Safety Check Upon completion of any service or repairs to this appliance, ask the service technician to perform safety checks to determine that the appliance is in proper operating condition.

#### **Specifications**

Input Impedance Max Input Level Input Connector	+15 dBu
Output Impedance Max Output Level Max Gain S/N Ratio	. 40mW in 100-Ohm 20dB/Channel . More than 90dB
THD Power Requirement Dimensions, WxHxD:	12V DC/150mA '4" (103.5 x 30 x 57 mm)

## PHA 40

### 4-Channel Stereo Headphone Amplifier

### FEATURES AND CONTROLS

#### **CONNECTION DIAGRAM**

